



NAS

Network Attached Storage
2 Bay Design

PX-NAS2 Series

GigaLAN

To continue addressing today's growing storage demand, Plextor proudly introduces a new line of versatile NAS devices that offer mass storage capacity, security, and accessibility of personal data anywhere, anytime within a home environment.

The Plextor PX-NAS2 network attached storage is designed for small office/home office and typical home users to conveniently and securely back up and organize digital collections such as videos, photos, music files in a central location.

The easy-to-use system comes with a Plextor PX-NAS2 utility software that smartly detects any PX-NAS2 attached to your network and starts to share, transfer, and download files with minimum configuration required. With the PX-NAS2, users can easily upload videos or photos to popular sites such as Flickr or YouTube to share with family and friends.

The PX-NAS2 is robust and secure. It allows the assigned administrator of the home network to define different levels of user access rights so that you can control who access what information stored in PX-NAS2 and how they can use it.

The Plextor PX-NAS2 comes in three options:

- PX-NAS2-BL1 two-bay NAS without Hard Disks
- PX-NAS2-1T1 two-bay NAS with 1TB, 2 x 500 GB Hard Disks
- PX-NAS2-2T1 two-bay NAS with 2TB, 2 x 1 TB Hard Disks

Easy Installation and Operation

- The automatic detection feature of bundled PX-NAS utility enables easy connection and setup in minutes with no technical knowledge required
- Imports or synchronizes contents from external digital cameras or USB drives with only one press of a button
- Supports Time Machine for easy back up for Mac systems
- Memeo auto backup software tool allows backup, sync and share content and information to multiple destinations simultaneously and automatically so personal digital life can be protected and accessible

Auto Recovery

- The system resumes automatically after power outage, so you don't have to worry about turning the PX-NAS2 back on
- Network connection and file transfer activities resume instantly after power recovery

Flexible Connectivity

- Easily upload or download files to or from most popular internet sites such as Flickr, YouTube and RSS broadcast sites
- DLNA 1.5 standard compliance for effortless "plug and play" connection with other compatible consumer electronic devices
- Media files and other public resources can be downloaded from the Internet via the BitTorrent, FTP or HTTP protocols without using a PC

Data Security

- The administrator can define different level of users access to the data stored in the network, allowing hassle-free network management and protection for professionals and small businesses without dedicated IT resource
- Encryption algorithm enforces data protection when transferring files between networks



Front Panel	
LED Light	Power/System/HDD/Copy
Backup Button	for USB device backup/sync
Power Button	Power on/off
USB Port	USB2.0 port for external devices
Rear Panel	
Power Connector	Connection for DC19V/1.5 A input
Network	RJ45 Ethernet connector
USB Port	USB2.0 port for external devices
Reset	Pin hole button for system reset
Dimensions and Weight	
Dimensions (W/H/D)	135.4 (W) x 120.3 (H) x 254.5 (D) mm 5.3 (W) x 4.7 (H) x 10.3 (D) inch
Weight	1.6 kg / 3.5 lbs (without HDD)

Package Contents	
Drive	PX-NAS2 2 Bay Network Attached Storage Device
Software	Support CD (including Memeo Backup Software)
Accessory	Power Adapter/Network case
Document	Quick installation guide and warranty statement

Certifications:	
Safety	UL1950, CAS C22.2 No.950, EN60950 EN41003
EMC	FCC Part 15 Class B, EN55022 Class B, C - Tick, VCCI, BSMI
Power Adapter	CEC Efficiency Level V Energy Star EFS Specification 2.0 Complied

Services Included	
Media Server with UPnP and DLNA 1.5 compliant	
iTunes [®] Server	
HTTP / FTP Server	
HTTPS / FTP over TLS (explicit encryption)	
SSL Certificate Management	
BitTorrent Client	
RSS Client / Server	
Backup Server with Memeo Autobackup Software	
IP Filter Management for BT / eMule	
USB Print Server	
USB UPS Power Monitoring	
Time Machine	

System Requirements	
Internal HDD	2 X bay support SATA I/II HDD up to 2TB each
Network Connection	1 X RJ45 port for 10/100/1000 Mbps connection
USB Connection	2 X USB2.0 ports
Power Adapter	100~240 V, 1.5A, 50~60Hz
OS Supported	Microsoft Windows [®] 2000/XP/ Vista/7; Windows [®] Server 2003; Linux Red Hat; Mac OS 10.4/10.5 * Bundled backup and media player software can only be operated on Microsoft OS
Browser Required	Microsoft Internet Explorer 6.0 or later; Firefox 2.0 or later; Netscape Navigator 7.0 or later
Operating Environment	41° F ~ 104° F with 20% ~ 95% RH 5° C ~ 40° C with 20% ~ 95% RH
Storage Environment	-22° F ~ 140° F with 5%~85% RH -30° C ~ 60° C with 5% ~ 85% RH



This market-leading service offers customers the fastest assistance:
2 Year (Collect & Return) warranty in the EU, Norway and Switzerland; 1 year in other countries: Carry-in.

Plextor

www.Plextor.com

© 2010 Copyright Plexor LLC.
Plextor Logo are registered trademark of Shinano Kabushiki Kaisha
Other brands and products are trademarks of their respective holders
Content subject to change without notices.